

Capitolo 9 - Input/Output formattato

Outline

- Introduzione
- Gli Stream
- Output formattato con `pri ntf`
- Stampa di interi
- Stampa di numeri Floating-Point
- Stampa di numeri e caratteri
- Altri indicatori di conversione
- Stampare con precisione
- Uso di Flags nella `pri ntf`
- Stampa di letterali e sequenze Escape
- Input formattato con la `scanf`

1

© Copyright 1992–2004 by Deitel & Associates, Inc. and Pearson Education Inc. All Rights Reserved.

Obiettivi

- In questo capitolo, impareremo a:
 - Capire gli stream di input e di output.
 - Utilizzare la formattazione di stampa.
 - Utilizzare l'input formattato.

2

© Copyright 1992–2004 by Deitel & Associates, Inc. and Pearson Education Inc. All Rights Reserved.

3

Introduzione

- In questo capitolo
 - Presentazione dei risultati
 - `scanf` e `pri ntf`
 - Gli Stream (input e output)
 - `gets`, `puts`, `getchar`, `putchar` (in `<stdi o. h>`)

4

Gli Stream

- Gli Stream
 - Sequenze di caratteri organizzate in linee
 - Ogni linea consiste di zero o più caratteri che termina con un carattere newline
 - L'ANSI C supporta linee di almeno 254 caratteri
 - Effettuano input e output
 - Possono essere ridezisionati
 - Standard input – keyboard
 - Standard output – screen
 - Standard error – screen

© Copyright 1992–2004 by Deitel & Associates, Inc. and Pearson Education Inc. All Rights Reserved.

© Copyright 1992–2004 by Deitel & Associates, Inc. and Pearson Education Inc. All Rights Reserved.

Formattare l'Output con la printf

- **printf**

- Output formattato
 - Specifiche di conversione: flags, dimensioni di campo, precisione, ecc.
- Può effettuare l'arrotondamento, l'allineamento delle colonne, giustificazione destra/sinistra, inserimento di caratteri letterale, formato esponenziale, formato esadecimale, e larghezza fissa e precisione

- Formattazione

- `printf(format-control-string, other-arguments);`
- Format control string: descrive il formato di output
- Other-arguments: corrispondono ad ogni specifica di conversione nella format-control-string
 - Ogni specifica inizia con il simbolo di percentuale (%), e termina con l'indicatore di conversione

© Copyright 1992–2004 by Deitel & Associates, Inc. and Pearson Education Inc. All Rights Reserved.

Stampa di interi

Conversion Specifier	Description
d	Display a signed decimal integer.
i	Display a signed decimal integer. (Note: The i and d specifiers are different when used with scanf.)
o	Display an unsigned octal integer.
u	Display an unsigned decimal integer.
x or X	Display an unsigned hexadecimal integer. X causes the digits 0–9 and the letters A–F to be displayed and x causes the digits 0–9 and a–f to be displayed.
h or l (letter l)	Place before any integer conversion specifier to indicate that a short or long integer is displayed respectively. Letters h and l are more precisely called <i>length modifiers</i> .

Fig. 9.1 Integer conversion specifiers.

© Copyright 1992–2004 by Deitel & Associates, Inc. and Pearson Education Inc. All Rights Reserved.

Stampa di interi

- Gli interi

- Intero numero (nessun punto decimale): 25, 0, -9
- Positivo, negativo, o zero
- Solo il segno meno viene stampato di default

© Copyright 1992–2004 by Deitel & Associates, Inc. and Pearson Education Inc. All Rights Reserved.



```

1 /* Fig. 9.2: fig09_02.c */
2 /* Using the integer conversion specifiers */
3 #include <stdio.h>
4
5 int main()
6 {
7     printf("sd\n", 455);
8     printf("%l\n", 455); /* l same as d in printf */
9     printf("%d\n", +455);
10    printf("%d\n", -455);
11    printf("hd\n", 32000);
12    printf("ld\n", 200000000);
13    printf("%o\n", 455);
14    printf("%u\n", 455);
15    printf("%u\n", -455);
16    printf("%x\n", 455);
17    printf("%X\n", 455);
18
19    return 0; /* indicates successful termination */
20
21 } /* end main */

```

© Copyright 1992–2004 by Deitel & Associates, Inc. and Pearson Education Inc. All Rights Reserved.

```
455  
455  
455  
-455  
32000  
2000000000  
707  
455  
4294966841  
1c7  
1c7
```

Stampa di numeri Floating-Point

Conversion specifier	Description
e or E	Display a floating-point value in exponential notation.
f	Display floating-point values.
g or G	Display a floating-point value in either the floating-point form f or the exponential form e (or E).
L	Place before any floating-point conversion specifier to indicate that a long double floating-point value is displayed.

Fig. 9.3 Floating-point conversion specifiers.

Stampare i numeri Floating-Point

- Numeri Floating Point
 - Hanno un punto decimale (33. 5)
 - Notazione esponenziale (la versione scientifica dei computer)
 - 150. 3 è 1. 503 × 10² in versione scientifica
 - 150. 3 è 1. 503E+02 in versione esponenziale (E sta per esponente)
 - usa e o E
 - f – stampa floating point con almeno una cifra a sinistra del decimale
 - g (o G) – stampa in f o e senza zero superflui (1. 2300 diventa 1. 23)
 - Usa l'esponenziale se l'esponente è minore di -4, o maggiore o uguale alla precisione (6 cifre di default)

```
1 /* Fig. 9.4: fig09_04.c */
2 /* Printing floating-point numbers with
3   floating-point conversion specifiers */
4
5 #include <stdio.h>
6
7 int main()
8 {
9     printf( "%e\n", 1234567.89 );
10    printf( "%e\n", +1234567.89 );
11    printf( "%e\n", -1234567.89 );
12    printf( "%E\n", 1234567.89 );
13    printf( "%f\n", 1234567.89 );
14    printf( "%g\n", 1234567.89 );
15    printf( "%G\n", 1234567.89 );
16
17    return 0; /* Indicates successful termination */
18
19 } /* end main */
```

```
1.234568e+006
1.234568e+006
-1.234568e+006
1.234568E+006
1234567.890000
1.23457e+006
1.23457E+006
```

9.6 Stampa di stringhe e caratteri

- C
 - Stampa argomenti char
 - Non può essere utilizzato per stampare il primo carattere di una stringa
- S
 - Richiede un puntatore a char come argomento
 - Stampa caratteri fino a NULL (' \0')
 - Non può stampare un argomento char
- Ricordare che
 - I singoli apici per caratteri costante (' z')
 - Doppi apici per le stringhe "z" (che in realtà contiene due caratteri, ' z' e ' \0')

© Copyright 1992–2004 by Deitel & Associates, Inc. and Pearson Education Inc. All Rights Reserved.

© Copyright 1992–2004 by Deitel & Associates, Inc. and Pearson Education Inc. All Rights Reserved.

```

1 /* Fig 9.5: fig09_05c */
2 /* Printing strings and characters */
3 #include <stdio.h>
4
5 int main()
6 {
7     char character = 'A'; /* Initialize char */
8     char string[] = "This is a string"; /* Initialize char array */
9     const char *stringPtr = "This is also a string"; /* char pointer */
10
11    printf( "%c\n", character );
12    printf( "%s\n", "This is a string" );
13    printf( "%s\n", string );
14    printf( "%s\n", stringPtr );
15
16    return 0; /* Indicates successful termination */
17
18 } /* end main */

```

A
 This is a string
 This is a string
 This is also a string

© Copyright 1992–2004 by Deitel & Associates, Inc. and Pearson Education Inc. All Rights Reserved.

Altri indicatori di conversione

- p
 - Visualizza il valore di un puntatore (indirizzo)
- n
 - Memorizza il numero di caratteri già visualizzati dalla `printf`
 - Ha un puntatore ad un intero come argomento
 - La specifica %n non stampa niente
 - Ogni chiamata a `printf` restituisce un valore
 - Numero di caratteri
 - Numero negativo in caso di errore
- %
 - Stampa il simbolo di percentuale
 - %%

© Copyright 1992–2004 by Deitel & Associates, Inc. and Pearson Education Inc. All Rights Reserved.

Altri indicatori di conversione

Conversion specifier	Description
p	Display a pointer value in an implementation-defined manner.
n	Store the number of characters already output in the current <code>printf</code> statement. A pointer to an integer is supplied as the corresponding argument. Nothing is displayed.
%	Display the percent character.

Fig. 9.6 Other conversion specifiers.

© Copyright 1992–2004 by Deitel & Associates, Inc. and Pearson Education Inc. All Rights Reserved.

```

1 /* Fig 9.7: fig09_07.c */
2 /* Using the p, n, and % conversion specifiers */
3 #include <stdio.h>
4
5 Int main()
6 {
7     Int *ptr;      /* define pointer to int */
8     Int x = 12345; /* Initialize int x */
9     Int y;        /* define int y */
10
11    ptr = &x;      /* assign address of x to ptr */
12    printf( "The value of ptr is %p\n", ptr );
13    printf( "The address of x is %p\n\n", &x );
14
15    printf( "Total characters printed on this line:\n", &y );
16    printf( "%d\n\n", y );
17
18    y = printf( "This line has 28 characters\n" );
19    printf( "%d characters were printed\n\n", y );
20
21    printf( "Printing a %% in a format control string\n" );
22
23    return 0; /* indicates successful termination */
24
25 } /* end main */

```

© Copyright 1992–2004 by Deitel & Associates, Inc. and Pearson Education Inc. All Rights Reserved.

 [Outline](#)
 [fig09_07.c \(1 of 2\)](#)

17

The value of ptr is 0012FF78
The address of x is 0012FF78

Total characters printed on this line: 38
This line has 28 characters
28 characters were printed
Printing a % in a format control string

 [Outline](#)
 [Program Output](#)

18

© Copyright 1992–2004 by Deitel & Associates, Inc. and Pearson Education Inc. All Rights Reserved.

19

Precisione

- Dimensioni di campo
 - La dimensione di campo da stampare
 - Se la dimensione è maggiore del dato viene utilizzato il valore di default
 - Se la dimensione del campo è troppo piccola, viene aumentata per contenere il dato
 - Il segno meno usa una posizione carattere nel campo
 - Le dimensioni intere inserite fra % e l'indicatore di conversione
 - %4d – dimensione di campo 4

© Copyright 1992–2004 by Deitel & Associates, Inc. and Pearson Education Inc. All Rights Reserved.

Precisione

- Precisione
 - Il significato varia in base al tipo di dato
 - Interi (default 1)
 - Minimo numero di cifre da stampare
 - Se il dato è troppo piccolo, viene prefisso da zeri
 - Floating point
 - Numero di cifre che devono apparire dopo il decimale (e e f)
 - per g – massimo numero di cifre significative
 - Stringhe
 - Massimo numero di caratteri della stringa da stampare
 - Formato
 - Utilizzare un punto (.) prima della precisione
%. 3f

© Copyright 1992–2004 by Deitel & Associates, Inc. and Pearson Education Inc. All Rights Reserved.

20

Precisione

- Dimensione di campo e precisione
 - Possono essere specificati entrambi
 - %*w* *d*.*p* precisi on
%5.3f
 - dimensione di campo negativa – giustificato a sinistra
 - dimensione di campo positiva – giustificato a destra
 - La precisione deve essere positiva
 - Possono essere utilizzati gli interi per determinare la dimensione di campo e la precisione
 - Posizionare l'asterisco (*) in luogo della dimensione di campo o della precisione
 - Confrontato ad un argomento int nella lista degli argomenti
 - Esempio:

```
printf( "%*. *f", 7, 2, 98.736 );
```

© Copyright 1992–2004 by Deitel & Associates, Inc. and Pearson Education Inc. All Rights Reserved.

```
1 /* Fig 9.8: fig09_08.c */
2 /* Printing Integers right-justified */
3 #include <stdio.h>
4
5 int main()
6 {
7     printf( "%4d\n", 1 );
8     printf( "%4d\n", 12 );
9     printf( "%4d\n", 123 );
10    printf( "%4d\n", 1234 );
11    printf( "%4d\n\n", 12345 );
12
13    printf( "%4d\n", -1 );
14    printf( "%4d\n", -12 );
15    printf( "%4d\n", -123 );
16    printf( "%4d\n", -1234 );
17    printf( "%4d\n", -12345 );
18
19    return 0; /* Indicates successful termination */
20
21 } /* end main */
```

```
1
12
123
1234
12345

-1
-12
-123
-1234
-12345
```

```
1 /* Fig 9.9: fig09_09.c */
2 /* Using precision while printing integers,
3    floating-point numbers, and strings */
4 #include <stdio.h>
5
6 int main()
7 {
8     int I = 873; /* Initialize int I */
9     double f = 123.94536; /* Initialize double f */
10    char s[] = "Happy Birthday"; /* Initialize char array s */
11
12    printf( "Using precision for integers\n" );
13    printf( "\t%.4d\n\t%.9d\n\n", I, I );
14
15    printf( "Using precision for floating-point numbers\n" );
16    printf( "\t%.3f\n\t%.3e\n\t%.3g\n\n", f, f, f );
17
18    printf( "Using precision for strings\n" );
19    printf( "\t%.11s\n", s );
20
21    return 0; /* Indicates successful termination */
22
23 } /* end main */
```

© Copyright 1992–2004 by Deitel & Associates, Inc. and Pearson Education Inc. All Rights Reserved.

© Copyright 1992–2004 by Deitel & Associates, Inc. and Pearson Education Inc. All Rights Reserved.

```
0873
000000873
```

```
123.945
1.239e+002
124
```

```
Happy Birth
```

Uso di Flag in printf

- Flag

- Ulteriori possibilità di formattazione
 - Posizionare un flag immediatamente a destra del simbolo percentuale
 - È possibile combinare più flag
- | Flag | Description |
|-------------------|--|
| - (minus sign) | Left-justify the output within the specified field. |
| + (plus sign) | Display a plus sign preceding positive values and a minus sign preceding negative values. |
| space | Print a space before a positive value not printed with the + flag. |
| # | Prefix 0 to the output value when used with the octal conversion specifier o. |
| 0x or 0X | Prefix 0x or 0X to the output value when used with the hexadecimal conversion specifiers x or X. |
| . (decimal point) | Force a decimal point for a floating-point number printed with e, E, f, g or G that does not contain a fractional part. (Normally the decimal point is only printed if a digit follows it.) For g and G specifiers, trailing zeros are not eliminated. |
| 0 (zero) | Pad a field with leading zeros. |

Fig. 9.10 Format control string flags.

```
1 /* Fig. 9.11: fig09_11.c */
2 /* Right justifying and left justifying values */
3 #include <stdio.h>
4
5 int main()
6 {
7     printf( "%10s%10d%10c%10f\n\n", "hello", 7, 'a', 1.23 );
8     printf( "%-10s%-10d%-10c%-10f\n", "hello", 7, 'a', 1.23 );
9
10    return 0; /* Indicates successful termination */
11
12 } /* end main */
13
14 hello      7      a   1.230000
15 hello      7      a   1.230000
```

```
1 /* Fig. 9.12: fig09_12.c */
2 /* Printing numbers with and without the + flag */
3 #include <stdio.h>
4
5 int main()
6 {
7     printf( "%d\n%d\n", 786, -786 );
8     printf( "%+d\n%+d\n", 786, -786 );
9
10    return 0; /* Indicates successful termination */
11
12 } /* end main */
13
14 786
15 -786
16 +786
17 -786
```

```

1 /* Fig 9.13: fig09_13.c */
2 /* Printing a space before signed values
3  not preceded by + or - */
4 #include <stdio.h>
5
6 int main()
7 {
8     printf( "%d\n% d\n", 547, -547 );
9
10    return 0; /* Indicates successful termination */
11
12 } /* end main */
13
14 547
15 -547

```



Outline

29

fig09_13.c

Program Output

© Copyright 1992–2004 by Deitel & Associates, Inc. and Pearson Education Inc. All Rights Reserved.

```

1 /* Fig 9.14: fig09_14.c */
2 /* Using the # flag with conversion specifiers
3  o, x, X and any floating-point specifier */
4 #include <stdio.h>
5
6 int main()
7 {
8     int c = 1427;      /* Initialize c */
9     double p = 1427.0; /* Initialize p */
10
11    printf( "%#o\n", c );
12    printf( "%#x\n", c );
13    printf( "%#X\n", c );
14    printf( "\n%g\n", p );
15    printf( "%#g\n", p );
16
17    return 0; /* Indicates successful termination */
18
19 } /* end main */

```

02623
0x593
0X593

1427
1427.00



Outline

30

fig09_14.c

Program Output

© Copyright 1992–2004 by Deitel & Associates, Inc. and Pearson Education Inc. All Rights Reserved.

```

1 /* Fig 9.15: fig09_15.c */
2 /* Printing with the 0( zero ) flag fills in leading zeros */
3 #include <stdio.h>
4
5 int main()
6 {
7     printf( "+%09d\n", 452 );
8     printf( "%09d\n", 452 );
9
10    return 0; /* Indicates successful termination */
11
12 } /* end main */
13
14 +000000452
15 000000452

```



Outline

31

fig09_15.c

Program Output

© Copyright 1992–2004 by Deitel & Associates, Inc. and Pearson Education Inc. All Rights Reserved.

Stampa di letterali e sequenze Escape

- Stampa di letterali
 - Possono essere stampati più caratteri
 - Problemi con alcuni caratteri come il simbolo "
 - Devono essere rappresentati con sequenze escape
 - Rappresentato da un backslash \ seguito da un carattere escape

© Copyright 1992–2004 by Deitel & Associates, Inc. and Pearson Education Inc. All Rights Reserved.

32

Stampa di letterali e sequanze Escape

Escape sequence	Description
\'	Output the single quote (') character.
\\"	Output the double quote (") character.
\?	Output the question mark (?) character.
\\\	Output the backslash (\) character.
\a	Cause an audible (bell) or visual alert.
\b	Move the cursor back one position on the current line.
\f	Move the cursor to the start of the next logical page.
\n	Move the cursor to the beginning of the next line.
\r	Move the cursor to the beginning of the current line.
\t	Move the cursor to the next horizontal tab position.
\v	Move the cursor to the next vertical tab position.

Fig. 9.16 Escape sequences.

Formattazione dell'Input con scanf

Conversion specifier	Description
<i>Integers</i>	
d	Read an optionally signed decimal integer. The corresponding argument is a pointer to integer.
i	Read an optionally signed decimal, octal, or hexadecimal integer. The corresponding argument is a pointer to integer.
o	Read an octal integer. The corresponding argument is a pointer to unsigned integer.
u	Read an unsigned decimal integer. The corresponding argument is a pointer to unsigned integer.
x or X	Read a hexadecimal integer. The corresponding argument is a pointer to unsigned integer.
h or l	Place before any of the integer conversion specifiers to indicate that a short or long integer is to be input.

Fig. 9.17 Conversion specifiers for scanf.

Formattazione dell'Input con scanf

Conversion specifier	Description
<i>Floating-point numbers</i>	
e, E, f, g or G	Read a floating-point value. The corresponding argument is a pointer to a floating-point variable.
l or L	Place before any of the floating-point conversion specifiers to indicate that a double or long double value is to be input.
<i>Characters and strings</i>	
c	Read a character. The corresponding argument is a pointer to char, no null ('\\0') is added.
s	Read a string. The corresponding argument is a pointer to an array of type char that is large enough to hold the string and a terminating null ('\\0') character—which is automatically added.
<i>Scan set</i>	
/scanf characters	Scan a string for a set of characters that are stored in an array.
<i>Miscellaneous</i>	
p	Read an address of the same form produced when an address is output with %p in a printf statement.
n	Store the number of characters input so far in this scanf. The corresponding argument is a pointer to integer.
%	Skip a percent sign (%) in the input.

Fig. 9.17 Conversion specifiers for scanf.

Formattazione dell'Input con scanf

- **scanf**
 - Input formattato
 - Possibilità
 - Input di tutti i tipi di dati
 - Input di specifici caratteri
 - Salta specifici caratteri
- **Formattazione**
 - **scanf(format-control-string, other-arguments);**
 - Format-control-string
 - Descrive il formato di input
 - Other-arguments
 - Puntatore alle variabili dove memorizzare l' input
 - Può includere dimensioni di campo per leggere uno specifico numero di caratteri dallo stream

Formattazione dell'Input con scanf

- Scan sets (insieme di scansione)
 - Insieme di caratteri racchiusi tra parentesi quadre []
 - Preceduti dal simbolo %
 - Scandisce stream di input, facendo riferimento solo ai caratteri nello scan set
 - Se occorre un matching, memorizza il carattere nell'array specificato
 - Si ferma solo quando incontra un carattere che non è nello scan set
 - Scan sets invertiti
 - Utilizzare ^: [^aeiou]
 - Vengono memorizzati i caratteri che non si trovano nello scan set
- Skipping characters
 - Include i caratteri da saltare nel controllo del formato
 - O, usa *
 - Salta ogni tipo di carattere senza memorizzarlo

© Copyright 1992–2004 by Deitel & Associates, Inc. and Pearson Education Inc. All Rights Reserved.



Outline

fig09_18.c

```

1 /* Fig 9.18: fig09_18.c */
2 /* Reading Integers */
3 #include <stdio.h>
4
5 int main()
6 {
7     int a; /* define a */
8     int b; /* define b */
9     int c; /* define c */
10    int d; /* define d */
11    int e; /* define e */
12    int f; /* define f */
13    int g; /* define g */
14
15    printf("Enter seven integers: ");
16    scanf("%d%d%d%d%d%d%d", &a, &b, &c, &d, &e, &f, &g);
17
18    printf("The Input displayed as decimal integers is:\n");
19    printf("%d %d %d %d %d %d\n", a, b, c, d, e, f, g);
20
21    return 0; /* Indicates successful termination */
22
23 } /* end main */

```

Program Output

```

Enter seven integers: -70 -70 070 0x70 70 70 70
The input displayed as decimal integers is:
-70 -70 56 112 56 70 112

```

© Copyright 1992–2004 by Deitel & Associates, Inc. and Pearson Education Inc. All Rights Reserved.

```

1 /* Fig 9.19: fig09_19.c */
2 /* Reading floating-point numbers */
3 #include <stdio.h>
4
5 /* function main begins program execution */
6 int main()
7 {
8     double a; /* define a */
9     double b; /* define b */
10    double c; /* define c */
11
12    printf("Enter three floating-point numbers: \n");
13    scanf("%lf%lf%lf", &a, &b, &c);
14
15    printf("Here are the numbers entered in plain\n");
16    printf("floating-point notation: \n");
17    printf("%f\n%f\n%f\n", a, b, c);
18
19    return 0; /* Indicates successful termination */
20
21 } /* end main */

```



Outline

fig09_19.c

© Copyright 1992–2004 by Deitel & Associates, Inc. and Pearson Education Inc. All Rights Reserved.



Outline

fig09_20.c

```

1 /* Fig 9.20: fig09_20.c */
2 /* Reading characters and strings */
3 #include <stdio.h>
4
5 int main()
6 {
7     char x; /* define x */
8     char y[9]; /* define array y */
9
10    printf("Enter a string: ");
11    scanf("%s", &x, y);
12
13    printf("The input was:\n");
14    printf("the character \"%c\"\n", x);
15    printf("and the string \"%s\"\n", y);
16
17    return 0; /* Indicates successful termination */
18
19 } /* end main */

```

Program Output

```

Enter a string: Sunday
The input was:
the character "S"
and the string "unday"

```

© Copyright 1992–2004 by Deitel & Associates, Inc. and Pearson Education Inc. All Rights Reserved.

```

1 /* Fig. 9.21: fig09_21.c */
2 /* Using a scan set */
3 #include <stdio.h>
4
5 /* function main begins program execution */
6 int main()
7 {
8     char z[ 9 ]; /* define array z */
9
10    printf( "Enter string: " );
11    scanf( "%[aeiou]", z ); /* search for set of characters */
12
13    printf( "The Input was \"%s\\n\", z );
14
15    return 0; /* indicates successful termination */
16
17 } /* end main */

```

Enter string: oeeooahah
The Input was "oeeooaa"

 [Outline](#)
 [fig09_21.c](#)

41

[Program Output](#)

```

1 /* Fig. 9.22: fig09_22.c */
2 /* Using an inverted scan set */
3 #include <stdio.h>
4
5 int main()
6 {
7     char z[ 9 ] = { '\\0' }; /* Initialize array z */
8
9     printf( "Enter a string: " );
10    scanf( "%[^aeiou]", z ); /* Inverted scan set */
11
12    printf( "The Input was \"%s\\n\", z );
13
14    return 0; /* indicates successful termination */
15
16 } /* end main */

```

Enter a string: String
The Input was "Str"

 [Outline](#)
 [fig09_22.c](#)

42

[Program Output](#)

© Copyright 1992–2004 by Deitel & Associates, Inc. and Pearson Education Inc. All Rights Reserved.

© Copyright 1992–2004 by Deitel & Associates, Inc. and Pearson Education Inc. All Rights Reserved.

```

1 /* Fig. 9.23: fig09_23.c */
2 /* Inputting data with a field width */
3 #include <stdio.h>
4
5 int main()
6 {
7     int x; /* define x */
8     int y; /* define y */
9
10    printf( "Enter a six digit integer: " );
11    scanf( "%2d%d", &x, &y );
12
13    printf( "The integers input were %d and %d\\n", x, y );
14
15    return 0; /* indicates successful termination */
16
17 } /* end main */

```

Enter a six digit integer: 123456
The integers input were 12 and 3456

 [Outline](#)
 [fig09_23.c](#)

43

[Program Output](#)

```

1 /* Fig. 9.24: fig09_24.c */
2 /* Reading and discarding characters from the input stream */
3 #include <stdio.h>
4
5 int main()
6 {
7     int month1; /* define month1 */
8     int day1; /* define day1 */
9     int year1; /* define year1 */
10    int month2; /* define month2 */
11    int day2; /* define day2 */
12    int year2; /* define year2 */
13
14    printf( "Enter a date in the form mm-dd-yyyy: " );
15    scanf( "%d%*c%d%*c%d", &month1, &day1, &year1 );
16
17    printf( "month = %d day = %d year = %d\\n\\n", month1, day1, year1 );
18
19    printf( "Enter a date in the form mm/dd/yyyy: " );
20    scanf( "%d%*c%d%*c%d", &month2, &day2, &year2 );
21
22    printf( "month = %d day = %d year = %d\\n", month2, day2, year2 );
23
24    return 0; /* indicates successful termination */
25
26 } /* end main */

```

 [Outline](#)
 [fig09_24.c](#)

44

© Copyright 1992–2004 by Deitel & Associates, Inc. and Pearson Education Inc. All Rights Reserved.

© Copyright 1992–2004 by Deitel & Associates, Inc. and Pearson Education Inc. All Rights Reserved.

Enter a date in the form mm-dd-yyyy: 11-18-2003
month = 11 day = 18 year = 2003

Enter a date in the form mm/dd/yyyy: 11/18/2003
month = 11 day = 18 year = 2003



Outline

Program Output

45